

▶  
▶  
▶

SERIE  
SÉRIE  
SERIES

# CK-NT16S



## Serie CK-NT16S

- ▶ • Impresora matricial RS-232
- Cabezal Epson
- 16 columnas
- Temp. de trabajo: 0-40 °C 5-80%HR

### Formato del papel

- Ancho del papel (mm): 44,5
- Grosor del papel (mm): 0.06-0.085
- Diámetro máximo papel (mm): 50
- Diámetro del mandril (mm): 10-12

- ▶ • Imprimante matricielle RS-232
- En tête Epson
- 16 colonnes
- Temp. de travail : 0-40 °C 5-80% HR

### Format de papier

- Largeur du papier (mm): 44,5
- Epaisseur du papier (mm): 0.06-0.0085
- Diamètre maximum du papier (mm): 50
- Diamètre du mandrin (mm): 10-12



- ▶ • Matricial printer: RS-232
- Heading Epson
- 16 columns
- Temperature of work: 0-40 °C 5-80% HR

### Papel format

- Width of paper (mm): 44,5
- Thickness of paper (mm): 0.06-0.0085
- Maximum diameter of paper (mm): 50
- Diameter of chuck (mm): 10-12

Código	Modelo	Descripción	Dim. total (mm)	Alimentación	Peso (g)
Code	Modèle	Description	Dim. total (mm)	Alimentation	Poids (g)
Code	Model	Description	Total dim. (mm)	Power	Weight (g)
5264	CK-NT16S	Conectable a indicadores SXS, SXB, IS, ISB, KI y IX	123 x 165 x 66	Alimentador 220/5V - 2A	150-380
	CK-NT16S	Connectable à indicateur SXS,SXB, IS,ISB, KI et IX			
	CK-NT16S	Conectable to indicator SXS,SXB, IS, ISB, K and IX			

